

## Medical Display



## SLH-PN015F-WB

## Main Features

- Power input range from 9-19V DC
- 15 Watt power
- IPx3 waterproof housing with Anti-Bacterial coating
- Slim and light weight housing
- Anti Glare glass display



## Specification

Display  15 inch TFT LED Anti Glare glass  Size  560 x 410 x 150 mm  Resolution  1024 x 768  Pixel Pitch  0.297 x 0.297 (one per triad)  Active screen area  307.4 (H) x 231.3 (V)  Contrast Ratio  2000 (Typ)  Luminance  300 cd/m²  Optical response time  5ms  Enclosure  IPx3 waterprotected Anti-bacterial  Connection  HDMI, VGA, DVI-D  Power  12V DC medical adapter  Power consumption  15Watts  VESA  75/100mm VESA mount  Operating temperature  0°C to 40°C  Storage temperature  -20°C to +60°C  Compliance  CE, FCC, RoHS  Weight		
Size 560 x 410 x 150 mm  Resolution 1024 x 768  Pixel Pitch 0.297 x 0.297 (one per triad)  Active screen area 307.4 (H) x 231.3 (V)  Contrast Ratio 2000 (Typ)  Luminance 300 cd/m²  Optical response time 5ms  Enclosure IPx3 waterprotected Anti-bacterial  Connection HDMI, VGA, DVI-D  Power 12V DC medical adapter  Power consumption 15Watts  VESA 75/100mm VESA mount  Operating temperature 0°C to 40°C  Storage temperature -20°C to +60 °C  Compliance CE, FCC, RoHS	Display	
Resolution 1024 x 768 Pixel Pitch 0.297 x 0.297 (one per triad) Active screen area 307.4 (H) x 231.3 (V)  Contrast Ratio 2000 (Typ) Luminance 300 cd/m²  Optical response time 5ms Enclosure IPx3 waterprotected Anti-bacterial Connection HDMI, VGA, DVI-D  Power 12V DC medical adapter  Power consumption 15Watts  VESA 75/100mm VESA mount  Operating temperature 0°C to 40°C  Storage temperature -20°C to +60°C  Compliance CE, FCC, RoHS	. ,	Anti Glare glass
Pixel Pitch  0.297 x 0.297 (one per triad)  Active screen area  307.4 (H) x 231.3 (V)  Contrast Ratio  2000 (Typ)  Luminance  300 cd/m²  Optical response time  5ms  Enclosure  IPx3 waterprotected Anti-bacterial  Connection  HDMI, VGA, DVI-D  Power  12V DC medical adapter  Power consumption  15Watts  VESA  75/100mm VESA mount  Operating temperature  0°C to 40°C  Storage temperature  -20°C to +60°C  Compliance  Contraction  0.200 (Typ)  200 (Typ)  2	Size	560 x 410 x 150 mm
Active screen area 307.4 (H) x 231.3 (V)  Contrast Ratio 2000 (Typ)  Luminance 300 cd/m²  Optical response time 5ms  Enclosure IPx3 waterprotected Anti-bacterial  Connection HDMI, VGA, DVI-D  Power 12V DC medical adapter  Power consumption 15Watts  VESA 75/100mm VESA mount  Operating temperature 0°C to 40°C  Storage temperature -20°C to +60°C  Compliance CE, FCC, RoHS	Resolution	1024 x 768
Contrast Ratio 2000 (Typ)  Luminance 300 cd/m²  Optical response time 5ms  Enclosure IPx3 waterprotected Anti-bacterial  Connection HDMI, VGA, DVI-D  Power 12V DC medical adapter  Power consumption 15Watts  VESA 75/100mm VESA mount  Operating temperature 0°C to 40°C  Storage temperature -20°C to +60°C  Compliance CE, FCC, RoHS	Pixel Pitch	
Luminance 300 cd/m²  Optical response time 5ms  Enclosure IPx3 waterprotected Anti-bacterial  Connection HDMI, VGA, DVI-D  Power 12V DC medical adapter  Power consumption 15Watts  VESA 75/100mm VESA mount  Operating temperature 0°C to 40°C  Storage temperature -20°C to +60°C  Compliance CE, FCC, RoHS	Active screen area	307.4 (H) x 231.3 (V)
Optical response time  Enclosure  IPx3 waterprotected Anti-bacterial  Connection  HDMI, VGA, DVI-D  Power  12V DC medical adapter  Power consumption  15Watts  VESA  75/100mm VESA mount  Operating temperature  0°C to 40°C  Storage temperature  -20°C to +60°C  Compliance  CE, FCC, RoHS	Contrast Ratio	2000 (Typ)
Enclosure  IPx3 waterprotected Anti-bacterial  Connection  HDMI, VGA, DVI-D  Power  12V DC medical adapter  Power consumption  15Watts  VESA  75/100mm VESA mount  Operating temperature  0°C to 40°C  Storage temperature  -20°C to +60°C  Compliance  CE, FCC, RoHS	Luminance	300 cd/m <sup>2</sup>
Anti-bacterial  Connection HDMI, VGA, DVI-D  Power 12V DC medical adapter  Power consumption 15Watts  VESA 75/100mm VESA mount  Operating temperature 0°C to 40°C  Storage temperature -20°C to +60°C  Compliance CE, FCC, RoHS	Optical response time	5ms
Power consumption 15Watts  VESA 75/100mm VESA mount  Operating temperature 0°C to 40°C  Storage temperature -20°C to +60°C  Compliance CE, FCC, RoHS	Enclosure	•
Power consumption 15Watts  VESA 75/100mm VESA mount  Operating temperature 0°C to 40°C  Storage temperature -20°C to +60°C  Compliance CE, FCC, RoHS	Connection	HDMI, VGA, DVI-D
VESA 75/100mm VESA mount  Operating temperature 0°C to 40°C  Storage temperature -20°C to +60°C  Compliance CE, FCC, RoHS	Power	12V DC medical adapter
Operating temperature  O°C to 40°C  Storage temperature  -20°C to +60°C  Ce, FCC, RoHS	Power consumption	15Watts
Storage temperature -20°C to +60 °C  Compliance CE, FCC, RoHS	VESA	75/100mm VESA mount
Compliance CE, FCC, RoHS	Operating temperature	0°C to 40°C
	Storage temperature	-20°C to +60 °C
Weight 5kg	Compliance	CE, FCC, RoHS
	Weight	5kg

All product specifications are subject to change without notice